

DEPENDENT RESURVEY OF THE WEST BOUNDARY, T. 16 N., R. 61 E.

CHAINS	
	Dependent Resurvey of the West Boundary, T. 16 N., R. 61 E.
	Reestablishment of the Survey Executed by E. B. Monroe, Deputy Surveyor, in 1869
	<p>Note: This line was originally surveyed as a common boundary, but due to excessive discrepancies in the original distances and bearings, the corners as originally established will no longer serve as corners for T. 16 N., R. 60 E. Therefore, the new iron post monuments at all recovered and proportionate corner positions are marked for sections of T. 16 N., R. 61 E. only. Corners for sections of T. 16 N., R. 60 E., are established along this line at 40.00 and 80.00 chain intervals, counting from the Standard Corner of secs. 36 and 31, Tps. 16 N., R. 60 and 61 E.</p> <p>From the standard corner of secs. 36 and 31, Tps. 16 N., R. 60 and 61 E., monumented with an iron post, 2½ ins. diam., firmly set, marked and witnessed as described in the official record.</p> <p>N. 0° 24' E., on the W. bdy. of sec. 31, T. 16 N., R. 61 E.</p> <p>Over slightly rolling land, through sparse timber, and medium heavy undergrowth; desc. 30 ft. over a WNW. slope.</p>
35.30	Wash, 10 lks. wide, 3 ft. deep, drains SW.
40.00	Point for the E. ¼ sec. cor. of sec. 36, T. 16 N., R. 60 E., at 40 chs. northing from the standard corner of Tps. 16 N., R. 60 and 61 E. Set an iron post, 36 ins. long, 1 in diam., 30 ins. in the ground, with brass cap mkd.
	<pre> T16N ½ R60E R61E S 36 1963 </pre>
	raise a mound of stone, 3½ ft. base, 3 ft. high, W. of cor.
40.50	The original ¼ sec. cor. of secs. 36 and 31, monumented with the rotted remains of an old squared wooden post, 3 ins. diam., found in the center of an old mound of earth and stone. This corner will now function for the ¼ sec. cor. of sec. 31, only.
	At the corner point Set an iron post, 36 ins. long, 1 in. diam., 20 ins. in the ground to solid rock, and in a collar of stone to top, with brass cap mkd.
	<pre> T16N ½ R60E R61E S 31 1963 </pre>