

DEPENDENT RESURVEY OF THE WEST BOUNDARY, T. 16 N., R. 61 E.

CHAINS

81.01 The original cor. of secs. 1, 6, 7, and 12, monumented with a squared wooden post, 3 ins. diam., firmly set, marked and witnessed as described in the official record. This corner will now function for the cor. of secs. 6 and 7, only.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

		T16N	
			R61E
R60E			
	S 1		S 6
			S 7
			1963

raise a mound of stone, 3 ft. base, 2 ft. high, E. of cor.

Land, gently rolling.

Soil, sandy and gravelly clay loam.

Timber, none; undergrowth, sagebrush, black brush, rabbit brush, with some greasewood and shadscale.

N. 0° 20' E., along the W. bdy. of sec. 6, T 16 N., R. 61 E.

Over slightly rolling land, through medium heavy undergrowth.

9.50 Wash, 20 lks. wide, 6 ft. deep, drains WSW.

34.93 Point for the E. ¼ sec. cor. of sec. 1, T. 16 N., R. 60 E., at 40.00 chs., northing from the cor. of secs. 1 and 12.

Set an iron post, 36 ins. long, 1 in. diam., 30 ins. in the ground, with brass cap mkd.

		T16N	
		¼	
R60E			R61E
	S 1		
			1963

raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.

40.51 The original ¼ sec. cor. of secs. 1 and 6, monumented with a squared wooden post, 4 ins. diam., firmly set, marked and witnessed as described in the official record. This corner will now function for the ¼ sec. cor. of sec. 6, only.

At the corner point

Set an iron post, 36 ins. long, 1 in. diam., 30 ins. in the ground, with brass cap mkd.