

SURVEY OF THE SUBDIVISIONAL LINES, T. 16 N., R. 60 E.

CHAINS	
80.00	<p>Point for the 1/16 sec. cor. of secs. 1 and 2.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T16N R60E 1/16 S 2 S 1 80 1963</p> <p>deposit broken glass around the iron post, 10 ins. below the surface of the ground.</p>
86.28	<p>Intersect S. bdy. of sec. 35, T. 17 N., R. 60 E.</p> <p>Point for the closing cor. of secs. 1 and 2.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T17N R60E S 35 S 2 S 1 T16N R60E CG 1963</p> <p>raise a mound of stone, 3½ ft. base, 2 ft. high, S. of cor. from which</p> <p>The cor. of secs. 35 and 36, T. 17 N., R. 60 E., monumented with an iron post, 2½ ins. diam., described in the field notes of the resurvey of the S. bdy. of T. 17 N., R. 60 E., executed concurrently with this survey, bears East, 2.96 chs. dist.</p> <p>The ¼ sec. cor. of sec. 35, T. 17 N., R. 60 E., monumented with an iron post, 1 in. diam., described in the field notes of the resurvey of the S. bdy. of T. 17 N., R. 60 E., executed concurrently with this survey, bears West, 37.04 chs. dist.</p> <p>Land, nearly level. Soil, sandy and gravelly clay loam. Timber, none; undergrowth, white sage, rabbit brush, black brush, with some shadscale and greasewood.</p>
	<p>The point for the N. ¼ sec. cor. of sec. 1 is at 40.00 chs., and on the N. bdy. of the Tp.</p> <p>At the corner point</p> <p>Set an iron post, 36 ins. long, 1 in. diam., 30 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T17N R60E ¼ S 1 T16N R60E 1963</p> <p>deposit broken glass around the iron post, 10 ins. below the surface of the ground.</p>