

## SURVEY OF THE SUBDIVISIONAL LINES, T. 16 N., R. 60 E.

CHAINS

T16N R60E

$$\begin{array}{c} \frac{1}{4} \\ S \ 3 \ | \ S \ 2 \\ 1963 \end{array}$$

deposit broken glass around the iron post, 10 ins. below the surface of the ground.

80.00 Point for the 1/16 sec. cor. of secs. 2 and 3.

Set an iron post, 36 ins. long, 1 in. diam., 30 ins. in the ground, with brass cap mkd.

T16N R60E

$$\begin{array}{c} 1/16 \\ S \ 3 \ | \ S \ 2 \\ 80 \\ 1963 \end{array}$$

raise a mound of stone, 3 ft. base, 1½ ft. high, W. of cor.

86.52 Intersect S. bdy. of sec. 34, T. 17 N., R. 60 E.

Point for the closing cor. of secs. 2 and 3.

Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, with brass cap mkd.

T17N R60E

$$\begin{array}{c} S \ 34 \\ \hline S \ 3 \ | \ S \ 2 \\ T16N \ R60E \\ CC \\ 1963 \end{array}$$

raise a mound of stone, 3 ft. base, 2 ft. high, S. of cor.

from which

The cor. of secs. 34 and 35, T. 17 N., R. 60 E., monumented with an iron post, 2½ ins. diam., described in the field notes of the resurvey of the S. bdy. of T. 17 N., R. 60 E., executed concurrently with this survey, bears East, 3.01 chs. dist.

The ¼ sec. cor. of sec. 34, T. 17 N., R. 60 E., monumented with an iron post, 1 in. diam., described in the field notes of the resurvey of the S. bdy. of T. 17 N., R. 60 E., executed concurrently with this survey, bears West, 36.99 chs. dist.

Land, nearly level.

Soil, sandy and gravelly clay loam.

Timber, none; undergrowth, white sage and sagebrush.

The point for the N. ¼ sec. cor. of sec. 2 is at midpoint and on the N. bdy. of the Tp.

At the corner point

Set an iron post, 36 ins. long, 1 in. diam., 30 ins. in the ground, with brass cap mkd.