

## SURVEY OF THE SUBDIVISIONAL LINES, T. 16 N., R. 60 E.

CHAINS	
59.30	Road, unimproved, bears NNW. and SSE.
79.96	The cor. of secs. 3, 4, 9, and 10.
	Land, nearly level. Soil, sandy and gravelly clay loam. Timber, none; undergrowth, white sage, sage brush and rabbit brush.
	N. 0° 01' W., bet. secs. 3 and 4.
	Over nearly level land, through medium heavy undergrowth.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 3 and 4.
	Set an iron post, 36 ins. long, 1 in. diam., 30 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T16N R60E  <math>\frac{1}{4}</math>  S 4   S 3  1963</p>
	raise a mound of stone, 2½ ft. base, 1½ ft. high, W. of cor.
75.90	Road, unimproved, bears NNW. and SSE.
80.00	Point for the 1/16 cor. of secs. 3 and 4.
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T16N R60E  1/16  S 4   S 3  80  1963</p>
	dig pits, 16x16x12 ins., N. and S. of post, 3 ft. dist., and raise a mound of earth, 2 ft. high, W. of cor.
86.86	Intersect S. bdy. of sec. 33, T. 17 N., R. 60 E.
	Point for the closing cor. of secs. 3 and 4.
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T17N R60E  S 33  S 4   S 3  T16N   R60E  CC  1963</p>
	raise a mound of stone, 2½ ft. base, 1½ ft. high, S. of cor.
	from which
	<p style="text-align: center;">The cor. of secs. 33 and 34, T. 17 N., R. 60 E., monumented with an iron post, 2½ ins. diam., described in the field notes of the resurvey of the S. bdy. of T. 17 N., R. 60 E., executed concurrently with this survey, bears East, 3.00 chs. dist.</p>