

SURVEY OF THE SUBDIVISIONAL LINES, T. 16 N., R. 60 E.

CHAINS		
39.98	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 4 and 9.</p> <p>Set an iron post, 36 ins. long, 1 in. diam., 30 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T16N R60E $\frac{1}{4}$ $\frac{S}{S}$ $\frac{4}{9}$ 1963</p> <p>dig pits, 16x16x12 ins., E. and W. of cor., 3 ft. dist.; raise a mound of earth, 2 ft. high, N. of cor.</p>	
47.60	<p>Fence, bears NNE. and SSE.</p>	
79.97	<p>The cor. of secs. 4, 5, 8, and 9.</p> <p>Land, nearly level. Soil, sandy and gravelly clay loam. Timber, none; undergrowth, white sage and sagebrush.</p>	
	<p>N. 0° 02' W., bet. secs. 4 and 5.</p> <p>Over nearly level land, through medium heavy undergrowth.</p>	
40.00	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 4 and 5.</p> <p>Set an iron post, 36 ins. long, 1 in. diam., 30 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T16N R60E $\frac{1}{4}$ S 5 S 4 1963</p> <p>raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.</p>	
80.00	<p>Point for the 1/16 cor. of secs. 4 and 5.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T16N R60E 1/16 S 5 S 4 80 1963</p> <p>deposit broken glass around the iron post, 6 ins. below the surface of the ground.</p>	
87.00	<p>Intersect the S. bdy. of sec. 32, T. 17 N., R. 60 E.</p> <p>Point for the closing cor. of secs. 4 and 5.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T17N R60E $\frac{S}{S}$ $\frac{32}{4}$ T16N R60E CC 1963</p> <p>raise a mound of stone, 3 ft. base, 2 ft. high, S. of cor.</p>	