

SURVEY OF THE SUBDIVISIONAL LINES, T. 16 N., R. 60 E.

CHAINS

T16N R60E
 1/16 $\frac{S \ 30}{S \ 31}$ 80
 1963

raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.

87.49 Intersect the E. bdy. of sec. 36, T. 16 N., R. 59 E.

Point for the closing cor. of secs. 30 and 31.

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T16N
 R59E | R60E
 S 36 | $\frac{S30C}{S31C}$
 1963

raise a mound of stone, 3 ft. base, 2½ ft. high, E. of cor.

from which

The cor. of secs. 25 and 36, T. 16 N., R. 59 E., monumented with an iron post, 2½ ins. diam., marked, set, and witnessed as described in the official record, bears N. 0° 19' E., 0.47 chs. dist.

The ¼ sec. cor. of sec. 36, T. 16 N., R. 59 E., monumented with an iron post, 2½ ins. diam., marked, set, and witnessed as described in the official record, bears S. 0° 19' W., 40.19 chs. dist.

Land, nearly level.
Soil, sandy and gravelly clay loam.
Timber, none; undergrowth, white sage and sagebrush.

The point for the W. ¼ sec. cor. of sec. 31 is at midpoint and on the W. bdy. of the Tp.

At the corner point

Set an iron post, 26 ins. long, 1 in. diam., 30 ins. in the ground, with brass cap mkd.

T16N
 ¼
 R59E | R60E
 S 31
 1963

deposit broken glass around the iron post, 6 ins. below the surface of the ground.

From this corner, the ¼ sec. cor. of sec. 36, T. 16 N., R. 59 E., bears S. 0° 19' W., 9 lks. dist.