

SURVEY OF THE SUBDIVISIONAL LINES, T. 16 N., R. 60 E.

CHAINS	<p>West, bet. secs. 19 and 30.</p> <p>Over nearly level land, through light low undergrowth.</p> <p>12.20 Road, unimproved, bears NW. and SE.</p> <p>40.00 Point for the 1/4 sec. cor. of secs. 19 and 30.</p> <p>Set an iron post, 36 ins. long, 1 in. diam., 30 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T16N R60E 1/4 S 19 S 30 1963</p> <p>deposit broken glass around the iron post, 10 ins. below the surface of the ground.</p> <p>80.00 Point for the 1/16 cor of secs. 19 and 30.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T16N R60E 1/16 S 19 80 S 30 1963</p> <p>raise a mound of stone, 3 ft. base, 1 1/2 ft. high, N. of cor.</p> <p>86.91 Intersect the E. bdy. of sec. 25, T. 16 N., R. 59 E.</p> <p>Point for the closing cor. of secs. 19 and 30.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T16N R59E R60E S 25 S 19 C S 30 C 1963</p> <p>raise a mound of stone, 3 ft. base, 2 ft. high, E. of cor. from which</p> <p style="margin-left: 40px;">The cor. of secs. 24 and 25, T. 16 N., R. 59 E., monumented with an iron post, 2 1/2 ins. diam., mkd., set and witnessed as described in the official record, bears N. 0° 16' E., 1.37 chs. dist.</p> <p style="margin-left: 40px;">The 1/4 sec. cor. of sec. 25, T. 16 N., R. 59 E., monumented with an iron post, 2 1/2 ins. diam., mkd., set and witnessed as described in the official record, bears S. 0° 16' W., 38.96 chs. dist.</p> <p>Land, nearly level. Soil, sandy and gravelly clay loam. Timber, none; undergrowth, white sage and sagebrush.</p> <hr/> <p>The point for the W. 1/4 sec. cor. of sec. 30 is at midpoint. and on the W. bdy. of the Tp.</p> <p>At the corner point</p> <p>Set an iron post, 36 ins. long, 1 in. diam., 30 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T16N 1/4 R59E R60E S 30 1963</p> <p>deposit broken glass around the iron post, 10 ins. below the surface of the ground.</p>
--------	---