

SURVEY OF THE SUBDIVISIONAL LINES, T. 16 N., R. 60 E.

CHAINS

85.19 Intersect E. bdy. of sec. 12, T. 16 N., R. 59 E.

Point for the closing cor. of secs. 6 and 7.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

	T16N	
		R60E
R59E		
S 12		S 6 C
		S 7 C
		1963

raise a mound of stone, 3 ft. base, 2 ft. high, E. of cor.
from which

The cor. of secs. 1 and 12, T. 16 N., R. 59 E.,
monumented with an iron post, $2\frac{1}{2}$ ins. diam., marked,
set, and witnessed as described in the official
record, bears N. $0^{\circ} 24'$ E., 4.26 chs. dist.

The $\frac{1}{4}$ sec. cor. of sec. 12, T. 16 N., R. 59 E.,
monumented with an iron post, $2\frac{1}{2}$ ins. diam., marked,
set, and witnessed as described in the official
record, bears S. $0^{\circ} 24'$ W., 36.26 chs. dist.

Land, nearly level.

Soil, sandy and gravelly clay loam.

Timber, none; undergrowth, white sage, sagebrush and greasewood.

The point for the W. $\frac{1}{4}$ sec. cor. of sec. 7 is at midpoint
and on the W. bdy. of the Tp.

At the corner point

Set an iron post, 36 ins. long, 1 in. diam., 30 ins. in the ground, with brass cap mkd.

	T16N	R60E
		$\frac{1}{4}$
		R60E
R59E		
		S 7
		1963

raise a mound of stone, $2\frac{1}{2}$ ft. base, $1\frac{1}{2}$ ft. high, E. of
cor.

From this corner, the $\frac{1}{4}$ sec. cor. of sec. 12, T. 16 N.,
R. 59 E., bears N. $0^{\circ} 15'$ E., 3.74 chs. dist.

The point for the W. $\frac{1}{4}$ sec. cor. of sec. 6 is located
40.00 chs. northing from the closing cor. of secs. 6 and
7, and on the W. bdy. of the Tp.

At the corner point

Set an iron post, 36 ins. long, 1 in. diam., 30 ins. in the ground, with brass cap mkd.