

## SURVEY OF THE SUBDIVISIONAL LINES, T. 16 N., R. 60 E.

CHAINS

T16N R60E

1/16

S 6 | S 5

80

1963

raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.

87.17 Intersect S. bdy. of sec. 31, T. 17 N., R. 60 E.

Point for the closing cor. of secs. 5 and 6.

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T17N R60E

S 31

S 6 | S 5

T16N | R60E

CG

1963

raise a mound of stone, 3 ft. base, 2 ft. high, S. of cor.

from which

The cor. of secs. 31 and 32, T. 17 N., R. 60 E., monumented with an iron post, 2½ ins. diam., described in the field notes of the resurvey of the S. bdy. of T. 17 N., R. 60 E., executed concurrently with this survey, bears East, 2.96 chs. dist.

The ¼ sec. cor. of sec. 31, T. 17 N., R. 60 E., monumented with an iron post, 1 in. diam., described in the field notes of the resurvey of the S. bdy. of T. 17 N., R. 60 E., executed concurrently with this survey, bears West, 37.04 chs. dist.

Land, nearly level.

Soil, sandy and gravelly clay loam.

Timber, none; undergrowth, white sage, sagebrush, black sage with some rabbit brush, shadscale and greasewood.

The point for the N. ¼ sec. cor. of sec. 5 is at midpoint and on the N. bdy. of the Tp.

At the corner point

Set an iron post, 36 ins. long, 1 in. diam., 30 ins. in the ground, with brass cap mkd.

T17N R60E

¼ S 5

T16N R60E

1963

deposit broken glass around the iron post, 10 ins. below the surface of the ground.

From this corner, the ¼ sec. cor. of sec. 32, T. 17 N., R. 60 E., heretofore described, bears East, 2.97 chs. dist.