

TOWNSHIP 17 NORTH, RANGE 60 EAST.

CHAINS

Independent Resurvey of the East Boundary - T. 17 N.,
R. 60 E.

Independent Resurvey Superseding the Survey Executed by
E. B. Monroe, Deputy Surveyor, in 1869.

Note: This line was originally surveyed as a common boundary for both adjoining townships, but because of the showing of gross irregularities in variance with the record, the corners as originally established will no longer serve as the corners. New monuments were established along this line at 40.00 and 80.00 chain intervals, counting from the corner of Tps. 16 and 17 N., Rs. 60 and 61 E. A diligent search was made for each original corner monument, and when found, a record of the bearing and distance from the new established corner is recorded in this field note record. After the point was found to be no longer needed, the original corners were then destroyed.

Beginning at the cor. of Tps. 16 and 17 N., Rs. 60 and 61 E., monumented with a squared wooden post, firmly set in the ground, marked and witnessed as described in the official record.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 17 N	
R60E	R61E
S 36	S 31
S 1	S 6
T 16 N	
1963	

raise a mound of stone, 5 ft. base, 3 ft. high, S. of cor. and reset the original corner post, alongside the iron post.

NORTH, on true line bet. secs. 31 and 36.

Over heavily rolling mountainous land, through sparse timber, and medium heavy undergrowth; asc. 170 ft. over a broken WSW. slope.

- | | |
|-------|--|
| 14.20 | Top of ascent, slopes WSW.; desc. 60 ft. over WNW. slope. |
| 19.10 | Head of ravine, drains W., begin ascent; asc. 20 ft. over WSW. slope. |
| 22.70 | Top of ascent; slopes WNW., begin descent; desc. 80 ft. over WNW. slope. |
| 30.00 | Bottom of descent; head of ravine, drains W., begin ascent; asc. 90 ft. over WSW. slope. |
| 39.90 | Top of spur, slopes NW. |
| 40.00 | Point for the ¼ sec. cor. of secs. 31 and 36. |