

INDEPENDENT RESURVEY OF THE EAST BOUNDARY, T. 17 N., R. 60 E.

CHAINS

Set an iron post, 28 ins. long, 2½ ins. diam., 18 ins. in the ground, to solid rock, and in a collar of stone to top, with brass cap mkd.

T 17 N
R60E R61E
S 1 | S 6
S 12 | S 7
1963

raise a mound of stone, 4 ft. base, 3 ft. high, W. of cor.

From this corner, the original cor. of secs. 1, 6, 7, and 12, monumented with a limestone, 12x10x6 ins., firmly set in the ground, marked and witnessed as described in the official record, bears N. 29° 41' E., 5.47 chs. dist. I destroyed all evidence of the original corner.

Land, gently rolling.
Soil, sandy and gravelly clay loam.
Timber, pinon and juniper; undergrowth, sagebrush, rabbit brush and shadscale.

North, bet. secs. 1 and 6.

Over gently rolling land, draining W., through medium heavy undergrowth.

- 1.00 Road, improved, on curve, from SSE. to NNW.
- 15.00 Same road, improved, bears SSW. and NE., enter scattering timber.
- 18.20 Wash, 10 lks. wide, 1 ft. deep, drains W., begin ascent; asc. 110 ft. over S. slope.
- 40.00 Point for the ¼ sec. cor. of secs. 1 and 6.

Set an iron post, 36 ins. long, 1 in. diam., 28 ins. in the ground, with brass cap mkd.

T 17 N
R60E R61E
¼
S 1 | S 6
1963

raise a mound of stone, 4 ft. base, 3 ft. high, W. of cor.

From this corner, the original ¼ sec. cor. of secs. 1 and 6, monumented with a trachyte stone, 24x14x12 ins. firmly set in the ground, marked and witnessed as described in the official record, bears N. 26° 20' E., 5.38 chs. dist. I destroyed all evidence of the original corner.

Continue over rolling mountainous land, through scattering timber and medium heavy undergrowth; continue ascent; asc. 794 ft. over SSE. slope.

- 66.98 Intersect S. bdy. of sec. 31, T. 18 N., R. 61 E.

Point for the closing cor. of Tps. 17 S., Rs. 60 and 61 E.