

INDEPENDENT RESURVEY OF THE SOUTH BOUNDARY, T. 17 N., R. 60 E.

CHAINS

West, along the S. bdy. of sec. 31.

Over nearly level land, through light undergrowth.

2.96 The closing corner of secs. 5 and 6, only, T. 16 N., R. 60 E., described in the field notes of the survey of the subdivisional lines of T. 16 N., R. 60 E., executed concurrently with this survey.

40.00 Point for the 1/4 sec. cor. of sec. 31, only.

Set an iron post, 36 ins. long, 1 in. diam., 30 ins. in the ground, with brass cap mkd.

T17N R60E  
 $\frac{1}{4}$  S 31  
 T16N R60E  
 1963

raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.

Continue over nearly level land, through light undergrowth.

42.96. The 1/4 sec. cor. of sec. 6, only, T. 16 N., R. 60 E., described in the field notes of the survey of the subdivisional lines of T. 16 N., R. 60 E., executed concurrently with this survey.

80.00 Point for the 1/16 sec. cor. of sec. 31.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T17N R60E  
 $\frac{1}{16}$  S 31  
 T16N R60E 80  
 1963

raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.

87.53 Intersect E. bdy. of sec. 36, T. 17 N., R. 59 E.

Point for the closing cor. of secs. 6 and 31.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T17N | T17N  
       | R60E  
 R59E | S 31 C  
 S 36 | S 6 C  
       | T16N  
       | R60E  
       |  
       1963

raise a mound of stone, 3 1/2 ft. base, 2 ft. high, E. of cor.

from which,

The cor. of Tps. 16 and 17 N., R. 59 E., monumented with an iron post, 2 1/2 ins. diam., firmly set in the ground, marked and witnessed as described in the official record, bears S. 0° 20' W., 2.11 chs. dist.