

SURVEY OF THE SUBDIVISIONAL LINES, T. 17 N., R. 60 E.

CHAINS	
	Continue over nearly level land; desc. 40 ft. over gradual W. slope through scattering timber, and medium heavy undergrowth.
79.95	The cor. of secs. 1, 2, 11, and 12. Land, nearly level. Soil, sandy and gravelly clay loam. Timber, pinon and juniper; undergrowth, sagebrush and rabbit brush.
	N. 0° 01' W., bet. secs. 1 and 2.
	Over nearly level land, through medium heavy undergrowth.
10.30	Wash, 20 lks. wide, 3 ft. deep, drains SW.; asc. 60 ft. over a WSW. slope.
25.00	Enter scattering timber, edge bears NW. and SE.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 1 and 2. Set an iron post, 36 ins. long, 1 in. diam., 20 ins. in the ground to solid rock, and in a mound of stone to top, with brass cap mkd.
	<p style="text-align: center;">T17N R60E $\frac{1}{4}$ S 2 S 1 1963</p>
	raise a mound of stone, 4 ft. base, 3 ft. high, W. of cor.
	Continue ascent; asc. 80 ft. over WSW. slope, through scattering timber and medium heavy undergrowth.
66.96	Intersect S. bdy. of sec. 36, T. 18 N., R. 60 E. Point for the closing cor. of secs. 1 and 2. Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 20 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T18N R60E S 36 S 2 S 1 T17N R60E CC 1963</p>
	raise a mound of stone, 4 ft. base, 3 ft. high, S. of cor.
	from which
	The cor. of secs. 35 and 36, T. 18 N., R. 60 E., monumented with an iron post, 2 $\frac{1}{2}$ ins. diam., firmly set, marked and witnessed as described in the official record, bears West, 8.98 chs. dist.
	The $\frac{1}{4}$ sec. cor. of sec. 36, T. 18 N., R. 60 E., monumented with an iron post, 1 in. diam., firmly set, marked and witnessed as described in the official record, bears East, 31.02 chs. dist.