

SURVEY OF THE SUBDIVISIONAL LINES, T. 17 N., R. 60 E.

CHAINS	
	<p>raise a mound of stone, 3½ ft. base, 2½ ft. high, W. of cor.</p> <p>Land, nearly level. Soil, sandy and gravelly clay loam. Timber, none; undergrowth, white sage and rabbit brush.</p>
20.70	<p>From the cor. of secs. 1, 2, 11, and 12.</p> <p>S. 89° 57' W., bet. secs. 2 and 11.</p> <p>Over nearly level land, through scattering undergrowth.</p> <p>Wash, 20 lks. wide, 3 ft. deep, drains WSW.</p>
40.04	<p>Point for the ¼ sec. cor. of secs. 2 and 11.</p> <p>Set an iron post, 36 ins. long, 1 in. diam., 30 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T17N R60E ¼ $\frac{S \ 2}{S \ 11}$ 1963</p>
52.40	<p>deposit broken glass around the iron post, 10 ins. below the surface of the ground.</p> <p>Continue over nearly level land, through medium heavy undergrowth.</p> <p>Road, improved, bears N. and S.</p>
80.08	<p>The cor. of secs. 2, 3, 10, and 11.</p> <p>Land, nearly level. Soil, sandy and gravelly clay loam. Timber, none; undergrowth, sagebrush, shadscale and rabbit brush.</p>
40.00	<p>N. 0° 01' W., bet. secs. 2 and 3.</p> <p>Over nearly level land, through light low undergrowth.</p> <p>Point for the ¼ sec. cor. of secs. 2 and 3.</p> <p>Set an iron post, 36 ins. long, 1 in. diam., 30 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T17N R60E ¼ $\frac{S \ 3 \ \ S \ 2}{1963}$</p>
67.04	<p>deposit broken glass around the iron post, 15 ins. below the surface of the ground.</p> <p>Continue over nearly level land, through scattering undergrowth.</p> <p>Intersect S. bdy. of sec. 35, T. 18 N., R. 60 E.</p> <p>Point for the closing cor. of secs. 2 and 3.</p>