

SURVEY OF THE SUBDIVISIONAL LINES, T. 17 N., R. 50 E.

CHAINS

Set an iron post, 36 ins. long, 1 in. diam., 30 ins. in the ground, with brass cap mkd.

T17N R60E
 $\frac{1}{2}$
 S 5 | S 4
 1963

deposit broken glass around the iron post, 6 ins. below the surface of the ground.

Continue over nearly level land, through medium heavy undergrowth.

62.50 Illipah Creek, 20 lks. wide, 3 ft. deep, dry, course SSE.

66.88 Intersect S. bdy. of sec. 33, T. 18 N., R. 60 E.

Point for the closing cor. of secs. 4 and 5.

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T18N R60E
S 33
 S 5 | S 4
 T17N R60E
 CC
 1963

raise a mound of stone, 3½ ft. base, 3 ft. high, S. of cor. from which

The cor. of secs. 32 and 33, T. 18 N., R. 60 S., monumented with an iron post, 2½ ins. diam., firmly set, marked and witnessed as described in the official record, bears West, 8.97 chs. dist.

The ¼ sec. cor. of sec. 33, T. 18 N., R. 60 E., monumented with an iron post, 1 in. diam., firmly set, marked and witnessed as described in the official record, bears East, 31.03 chs. dist.

Land, nearly level.
 Soil, sandy and gravelly clay loam.
 Timber, none; undergrowth, white sage, sagebrush, and rabbit brush.

The point for the N. ¼ sec. cor. of sec. 4 is at midpoint and on the N. bdy. of the Tp.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.

T18N R60E
 $\frac{1}{4}$ S 4
 T17N R60E
 1963

raise a mound of stone, 3½ ft. base, 3 ft. high, S. of cor.