

## SURVEY OF THE SUBDIVISIONAL LINES, T. 17 N., R. 60 E.

## CHAINS

West, bet. secs. 18 and 19.

Over nearly level land, through light undergrowth.

18.70 Wash, 15 lks. wide, 2 ft. deep, drains SE.

40.00 Point for the  $\frac{1}{4}$  sec. cor. of secs. 18 and 19.

Set an iron post, 36 ins. long, 1 in. diam., 30 ins. in the ground, with brass cap mkd.

T17N R60E  
 $\frac{1}{4}$   $\frac{S \ 18}{S \ 19}$   
 1963

deposit broken glass around the iron post, 6 ins. below the surface of the ground.

Continue over nearly level land, through light undergrowth.

80.00 Point for the  $\frac{1}{16}$  sec. cor. of secs. 18 and 19.

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground, with brass cap mkd.

T17N R60E  
 $\frac{1}{16}$   $\frac{S \ 18}{S \ 19}$  80  
 1963

raise a mound of stone,  $2\frac{1}{2}$  ft. base,  $1\frac{1}{2}$  ft. high, N. of cor.

85.70 Intersect E. bdy. of sec. 24, T. 17 N., R. 59 E.

Point for the closing cor. of secs. 18 and 19.

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground, with brass cap mkd.

T17N  
 R59E | R60E  
 S 24 |  $\frac{S \ 18}{S \ 19}$  C  
 1963

raise a mound of stone,  $2\frac{1}{2}$  ft. base,  $1\frac{1}{2}$  ft. high, E. of cor.

from which

The cor. of secs. 13 and 24, T. 17 N., R. 59 E., monumented with an iron post,  $2\frac{1}{2}$  ins. diam., firmly set, marked and witnessed as described in the official record, bears N.  $0^{\circ} 21'$  E., 0.18 chs. dist.

The  $\frac{1}{4}$  sec. cor. of sec. 24, T. 17 N., R. 59 E., monumented with an iron post,  $2\frac{1}{2}$  ins. diam., firmly set, marked and witnessed as described in the official record, bears S.  $0^{\circ} 21'$  W., 40.35 chs. dist.

Land, nearly level.

Soil, sandy and gravelly clay loam.

Timber, none; undergrowth, white sage, rabbit brush and sagebrush.