

SURVEY OF THE SUBDIVISIONAL LINES, T. 17 N., R. 60 E.

CHAINS

85.12 Intersect the E. bdy. of sec. 13, T. 17 N., R. 59 E.
 Point for the closing cor. of secs. 7 and 18.
 Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.

T17N	
R59E	R60E
S 13	S 7 C
	S 18 C
1963	

raise a mound of stone, $2\frac{1}{2}$ ft. base, $1\frac{1}{2}$ ft. high, E. of cor.

from which

The cor. of secs. 12 and 13, T. 17 N., R. 59 E., monumented with an iron post, $2\frac{1}{2}$ ins. diam., firmly set, marked and witnessed as described in the official record, bears N. $0^{\circ} 18' E.$, 0.92 chs. dist.

The $\frac{1}{4}$ sec. cor. of sec. 13, T. 17 N., R. 59 E., monumented with an iron post, $2\frac{1}{2}$ ins. diam., firmly set, marked and witnessed as described in the official record, bears S. $0^{\circ} 18' W.$, 39.39 chs. dist.

Land, nearly level.

Soil, sandy and gravelly clay loam.

Timber, none; undergrowth, white sage, rabbit brush and sagebrush.

The point for the W. $\frac{1}{4}$ sec. cor. of sec. 18, is at mid-point and on the W. bdy. of the Tp.

At the corner point

Set an iron post, 36 ins. long, 1 in. diam., 30 ins. in the ground, with brass cap mkd.

T17N	
	$\frac{1}{4}$
R59E	R60E
	S 18
1963	

deposit broken glass around the iron post, 6 ins. below the surface of the ground.

from which

The $\frac{1}{4}$ sec. cor. of sec. 13, T. 17 N., R. 59 E., bears N. $0^{\circ} 19' E.$, 0.61 chs. dist.

The cor. of secs. 13 and 24, T. 17 N., R. 59 E., bears S. $0^{\circ} 19' W.$, 39.83 chs. dist.

From the cor. of secs. 7, 8, 17, and 18.

N. $0^{\circ} 03' W.$, bet. secs. 7 and 8.

Over nearly level land, through light low undergrowth.

40.00 Point for the $\frac{1}{4}$ sec. cor. of secs. 7 and 8.