

SURVEY OF THE SUBDIVISIONAL LINES, T. 17 N., R. 60 E.

CHAINS	
40.00	<p>West, bet. secs. 6 and 7.</p> <p>Over nearly level land, through light low undergrowth.</p> <p>Point for the $\frac{1}{4}$ sec. cor. of secs. 6 and 7.</p> <p>Set an iron post, 36 ins. long, 1 in. diam., 30 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T17N R60E $\frac{1}{4}$ $\frac{S \ 6}{S \ 7}$ 1963</p> <p>deposit broken glass around the iron post, 10 ins. below the surface of the ground.</p> <p>Continue over nearly level land, through medium heavy undergrowth.</p>
80.00	<p>Point for the $\frac{1}{16}$ sec. cor. of secs. 6 and 7.</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T17N R60E $\frac{1}{16}$ $\frac{S \ 6}{S \ 7}$ 80 1963</p> <p>raise a mound of stone, $2\frac{1}{2}$ ft. base, $1\frac{1}{2}$ ft. high, N. of cor.</p>
84.53	<p>Intersect the E. bdy. of sec. 12, T. 17 N., R. 59 E.</p> <p>Point for the closing cor. of secs. 6 and 7.</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T17N R59E R60E S 12 S 6 C S 7 C 1963</p> <p>raise a mound of stone, $2\frac{1}{2}$ ft. base, $1\frac{1}{2}$ ft. high, E. of cor.</p> <p>from which</p> <p>The cor. of secs. 1 and 12, T. 17 N., R. 59 E., monumented with an iron post, $2\frac{1}{2}$ ins. diam., firmly set, marked and witnessed as described in the official record, bears N. $0^{\circ} 18' E.$, 1.77 chs. dist.</p> <p>The $\frac{1}{4}$ sec. cor. of sec. 12, T. 17 N., R. 59 E., monumented with an iron post, $2\frac{1}{2}$ ins. diam., firmly set, marked and witnessed as described in the official record, bears S. $0^{\circ} 18' W.$, 38.65 chs. dist.</p> <p>Land, nearly level. Soil, sandy and gravelly clay loam. Timber, none; undergrowth, white sage, rabbit brush and sagebrush.</p>