

SURVEY OF THE SUBDIVISIONAL LINES, T. 17 N., R. 60 E.

CHAINS

deposit broken glass around the iron post, 10 ins. below the surface of the ground.

Continue over nearly level land, through low undergrowth.

67.00

Intersect the S. bdy. of sec. 32, T. 18 N., R. 60 E.

Point for the closing cor. of secs. 5 and 6.

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T18N	R60E
S	32
S 6	S 5
T17N	R60E
GC	
1963	

raise a mound of stone, 2½ ft. base, 1½ ft. high, S. of cor.

from which

The cor. of secs. 31 and 32, T. 18 N., R. 60 E., monumented with an iron post, 2½ ins. diam., firmly set, marked and witnessed as described in the official record, bears West, 8.99 chs. dist.

The ¼ sec. cor. of sec. 32, T. 18 N., R. 60 E., monumented with an iron post, 1 in. diam., firmly set, marked and witnessed as described in the official record, bears East, 31.01 chs. dist.

Land, nearly level.

Soil, sandy and gravelly clay loam.

Timber, none; undergrowth, sagebrush, white sage, rabbit brush and mesquite.

The point for the N. ¼ sec. cor. of sec. 5 is at midpoint and on the N. bdy. of the Tp.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T18N	R60E
¼ S	5
T17N	R60E
1963	

raise a mound of stone, 3 ft. base, 2 ft. high, S. of cor.

from which

The ¼ sec. cor. of sec. 32, T. 18 N., R. 60 E., bears West, 8.98 chs. dist.

The cor. of secs. 32 and 33, T. 18 N., R. 60 E., bears East, 31.02 chs. dist.