

SURVEY OF THE SUBDIVISIONAL LINES, T. 17 N., R. 61 E.

CHAINS

EAST, bet. secs. 24 and 25.

Over gently rolling land, through medium heavy undergrowth; desc. 150 ft. over ENE. slope.

12.70 Road, unimproved, bears N. and S.

40.00 Point for the $\frac{1}{4}$ sec. cor. of secs. 24 and 25.Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 10 ins. in the ground to solid rock and in a mound of stone to top, with brass cap mkd.

T17N R61E

$\frac{1}{4}$	S	24
	S	25

1963

from which

A pinon, 8 ins. diam., bears S. 7° E., 55 lks. dist., mkd. T17N R61E $\frac{1}{4}$ S 25 BT.A pinon, 12 ins. diam., bears N. 60° W., 9 lks. dist., mkd. T17N R61E $\frac{1}{4}$ S 24 BT.

42.60 Top of spur, slopes N., begin descent; desc. 190 ft. over an ENE. slope.

66.00 Road, unimproved, bears NW. and SE., leave scattering timber.

83.44 Intersect the W. bdy. of sec. 19, T. 17 N., R. 62 E.

Point for the closing cor. of secs. 24 and 25.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T17N		
	R61E	
C	S 24	R62E
C	S 25	S 19
1963		

raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.

from which

The cor. of secs. 19 and 30, T. 17 N., R. 62 E., hereinbefore described, bears S. $0^{\circ} 35'$ W., 8.33 chs. dist.The $\frac{1}{4}$ sec. cor. of sec. 19, T. 17 N., R. 62 E., hereinbefore described, bears N. $0^{\circ} 35'$ E., 31.96 chs. dist.

Land, gently rolling.

Soil, sandy and gravelly clay loam.

Timber, pinon and juniper.

Undergrowth, sagebrush and mahogany.

The point for the E. $\frac{1}{4}$ sec. cor. of sec. 25 is at midpoint and on the E. bdy. of the Tp.

At the corner point