

DEPENDENT RESURVEY OF THE E. BDY., T. 3 S., R. 54 E.

CHAINS

T3S
R54E R55E
S 1 | S 6
S 12 | S 7
1964

bury the original cornerstone alongside the iron post.

Land, level.

Soil, sandy loam.

Undergrowth, greasewood and shadscale.

N. 0° 08' W., bet. secs. 1 and 6.

Over level land.

9.50 Trail road, bears NE. and SW.

31.10 Wash, 10 lks. wide, 2 ft. deep, drains SE.

40.27 The $\frac{1}{4}$ sec. cor. of secs. 1 and 6, monumented with a granite stone, 18x12x8 ins., plainly mkd. and firmly set.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 20 ins. in the ground and in a collar of stone, with brass cap mkd.

T3S
R54E R55E
 $\frac{1}{2}$
S 1 | S 6
1964

bury the original cornerstone alongside the iron post.

N. 0° 18' E., beginning new measurement.

1.20 Base of asc.; bears SW. and NE.; asc. 440 ft. along W. slope of ridge.

40.26 The cor. of Tps. 2 and 3 S., Rs. 54 and 55 E., monumented with a granite stone, 18x12x6 ins., plainly mkd. and firmly set.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 15 ins. in the ground to bedrock and in a mound of stone, 6 ft. base to top, with brass cap mkd.

T2S
R54E R55E
S 36 | S 31
S .1 | S 6
T3S
1964

bury the original cornerstone alongside the iron post.