

## DEPENDENT RESURVEY OF A PORTION OF THE N. BDY., T. 3 S., R. 54 E.

CHAINS

T2S R54E  
 $\frac{1}{4}$  S 34  
 S 3  
 T3S  
 1964

raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.

67.90 Nevada State Hwy., No. 25., bears N. 57° 40' W., and S. 57° 40' E.

79.94 The cor. of secs. 3, 4, 33 and 34, monumented with a limestone, 8x4x2 ins., plainly mkd. and firmly set.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground and in a collar of stone, with brass cap mkd.

T2S R54E  
 S33 | S 34  
 S 4 | S 3  
 T3S  
 1964

bury the original cornerstone alongside the iron post.

Land, rolling.  
 Soil, sandy loam.  
 Undergrowth, greasewood and shadscale.

Dependent Resurvey of a portion of the Subdivisional Lines,  
 T. 3 S., R. 54 E., Mount Diablo Meridian, Nevada

Re-establishment of the survey executed by  
 Reilly and Magee, Deputy Surveyors,  
 in 1881

From the cor. of secs. 1, 2, 35 and 36, on the S. Bdy. of the Tp.

N. 0° 08' W., bet. secs. 35 and 36.

Over level land.

40.37 Point for the ¼ sec. cor. of secs. 35 and 36, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground with brass cap mkd.

T3S R54E  
 $\frac{1}{4}$   
 S35 | S 36  
 1964

49.00 Wash, 15 lks. wide, 2 ft. deep, drains NE.

77.20 Wash, 15 lks. wide, 1 ft. deep, drains NE.