404

3

·	DEPEND	ENT RESURVEY OF A PORTION OF THE S. BDY., T. 3 S., R. 56 E.
	CHAINS	N. 89° 44' W., bet. secs. 6 and 31.
		Over rolling land; desc. a gentle NW. slope.
	2 7·•9 0	Nevada State Hwy. No. 25, bears N. 57° 40' W., and S. 57° 40' E.
	33.50	Old Hwy. bears NW. and SE.
	40.19	The $\frac{1}{2}$ sec. cor. of secs. 6 and 31, monumented with a limestone, $8x6x2$ ins., plainly mkd. and firmly set.
4		At the corner point
		Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 20 ins. in the ground and in a collar of stone, with brass cap mkd.
		$\begin{array}{ccc} T3S & R56E \\ \frac{1}{4} & \underline{S} & 31 \\ \hline 4 & \underline{S} & 6 \\ & T4S \\ & 1964 \end{array}$
		bury the original cornerstone alongside the iron post.
		N. 89° 50' W., beginning new measurement.
	.24.00	Wash, 10 lks. wide, 2 ft. deep, drains NW.
	42.37	The cor. of Tps. 3 and 4 S., Rs. 55 and 56 E., monumented with an iron post, $2\frac{1}{2}$ ins. diam., set, mkd. and witnessed as described in the field notes of the concurrent resurvey of T. 3 S., R. 55 E.
		Land, rolling. Soil, clay loam. Undergrowth, greasewood and cresote brush.
	•	Dependent Resurvey of a portion of the N. Bdy., T. 3 S., R. 56 E., Mount Diablo Meridian, Nevada
		Re-establishment of the survey executed by Reilly and Magee, Deputy Surveyors, in 1881.
		From the ½ sec. cor. of secs. 3 and 34, on the N. bdy. of the Tp., monumented with a limestone, 12x10x8 ins., plainly mkd. and firmly set.
		At the corner point
		Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd.
	···	T2S R56E <u>1 S 34</u> S 3 T3S
		1964
	, . <u> </u>	bury the original cornerstone alongside the iron post.
		N. 89° 36' W., bet. secs. 3 and 34.
		Over rolling land; desc. gentle W. slope.

-

•