

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES, T. 3 S., R. 56 E.

CHAINS
81.92

The cor. of secs. 25, 30, 31 and 36, on the W. bdy. of the Tp., monumented with an iron post, 2½ ins. diam., set, mkd. and witnessed as described in the field notes of the concurrent resurvey of T. 3 S., R. 55 E.

Land, level.
Soil, sandy loam.
Undergrowth, greasewood and shadscale.

From the cor. of secs. 29, 30, 31 and 32.

N. 0° 04' E., bet. secs. 29 and 30.

Over rolling land; desc. gradual N. slope.

23.90

Graded road, bears NE. and SW.

40.30

Point for the ¼ sec. cor. of secs. 29 and 30, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground and in a collar of stone, with brass cap mkd.

T3S R56E
¼
S30 | S 29
1964

from which:

A U. S. Geological Survey Bench Mark, bears S. 10° 40' E., 15.47 chs. dist. mkd.

1963
elevation
above sea
4886 feet
1JDC

A well bears S. 89° 30' E., 28.42 chs. dist.

A water tank, bears S. 89° 57' E., 28.70 chs. dist.

69.30

Graded road, bears NE. and SW.

80.60

Point for the cor. of secs. 19, 20, 29 and 30, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground and in a collar of stone, with brass cap mkd.

T3S R56E
S19 | S 20
S30 | S 29
1964

Land, rolling.
Soil, sandy loam.
Undergrowth, greasewood and shadscale.