DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES, T. 3 S., R. 56		
	CHAINS	m20 DECE
		T3S R56E
		$\frac{1}{4} \frac{S}{S} = \frac{17}{20}.$
		1964
	***	raise a mound of stone, 2 ft. base, 1½ ft. high, N. of cor.
	79.10	Trail road, bears N. 10° W., and S. 10° E.
	81.95	The cor. of secs. 17, 18, 19 and 20.
		Land, level. Soil, sandy loam. Undergrowth, greasewood and shadscale.
		S. 89° 51' W., bet. secs. 18 and 19.
•	·	Over level land.
	5.00	Wash, 20 lks, wide, 2 ft. deep, drains NW.
	37.20	Trail road, bears N. 70° W., and S. 70° E.
	40.88	Point for the ½ sec. cor. of secs. 18 and 19, at proportionate distance; there is no remaining evidence of the original corner.
		Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground with brass cap mkd.
		T3S R56E 2 S 18 S 19 1964
		raise a mound of stone, 2 ft. base, 1½ ft. high, N. of cor.
	80.54	The cor. of secs. 13, 18, 19 and 24, on the W. bdy. of the Tp., monumented with an iron post, 2½ ins. diam., set, mkd. and witnessed as described in the field notes of the concurrent resurvey of T. 3 S., R. 55 E.
		Land, level. Soil, sandy loam. Undergrowth, greasewood and shadscale.
		From the cor. of secs. 17, 18, 19 and 20.
		N. 0° 38 E., bet. secs. 17 and 18.
		Over level land.
	5.00	Trail road, bears N. 10° W., and S. 10° E.
	28.00	Wash, 15 lks. wide, 2 ft. deep, drains SW.
	40.30	Point for the ½ sec. cor. of secs. 17 and 18, at proportionate distance; there is no remaining evidence of the original corner.
	e Service de la companya de la compa	Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground with brass cap mkd.
		e e e e e e e e e e e e e e e e e e e