

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES, T. 3 S., R. 56 E.

CHAINS	
	T3S R56E $\frac{1}{4}$ S 7 S 18 1964
80.92	<p>The cor. of secs. 7, 12, 13 and 18, on the W. bdy. of the Tp., monumented with an iron post, 2½ ins. diam., set, mkd. and witnessed as described in the field notes of the concurrent resurvey of T. 3 S., R. 55 E.</p> <p>Land, level. Soil, sandy loam. Undergrowth, greasewood and shadscale.</p>
	<p>From the cor. of secs. 7, 8, 17 and 18.</p> <p>N. 0° 27' E., bet. secs. 7 and 8.</p> <p>Over level land.</p>
5.00	Wash, 15 lks. wide, 2 ft. deep, drains W.
40.30	<p>Point for the ¼ sec. cor. of secs. 7 and 8, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground and in a collar of stone, with brass cap mkd.</p>
	T3S R56E $\frac{1}{4}$ S 7 S 8 1964
80.60	<p>Point for the cor. of secs. 5, 6, 7 and 8, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground with brass cap mkd.</p>
	T3S R56E S 6 S 5 S 7 S 8 1964
	<p>raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.</p> <p>Land, level. Soil, sandy loam. Undergrowth, greasewood and shadscale.</p>
	<p>From the cor. of secs. 4, 5, 8 and 9.</p> <p>N. 89° 09' W., bet. secs. 5 and 8.</p> <p>Over level land.</p>
36.70	Graded road, bears N. and S.
40.51	<p>Point for the ¼ sec. cor. of secs. 5 and 8, at proportionate distance; there is no remaining evidence of the original corner.</p>