DEPENDENT RESURVEY	OF	A PORTION	OF	THE	SUBDIVISIONAL	LINES	т.	4 S.	, R.	55	Ε.
--------------------	----	-----------	----	-----	---------------	-------	----	------	------	----	----

CHAINS	IVEY OF A PORTION OF THE SUBBIVISIONAL LINES, T. 4'S., R. 55
CHAINS	from which
	A U. S. Geological Survey bench mark, bears N. 45° 25' W., 18.64 chs. dist., mkd. ET5LC.
55.70	Graded road, bears E. and W.
80.75	The cor. of secs. 1, 2, 35 and 36, on the N. bdy. of the Tp., monumented with an iron post, $2\frac{1}{2}$ ins. diam., set, mkd., and witnessed as described in the field notes of the concurrent resurvey of T. 3 S., R. 55 E.
• ,	Land, level. Soil, sandy loam. Undergrowth, greasewood and shadscale.
	From the cor. of secs. 11, 12, 13 and 14.
	S. 89° 37' W., bet. secs. 11 and 14.
	Over rolling land.
40.19	Point for the 1 sec. cor. of secs. 11 and 14, at proportionate distance; there is no remaining evidence of the original corner.
•	Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.
	T4S R55E S 11 S 14 1964
•	raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.
80.39	The cor. of secs. 10, 11, 14 and 15, monumented with a limestone, 12x12x10 ins., plainly mkd. and firmly set.
	At the corner point
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground and in a collar of stone, with brass cap mkd.
	T4S R55E
	S 10 S 11 S 15 S 14 1964
	bury the original cornerstone alongside the iron post.
	Land, rolling. Soil, clay loam, rocky.
_	Undergrowth, greasewood and cresote brush.
	N. 0° 09' E., bet. secs. 10 and 11.
	Over rolling land.
27.40	Wash, 15 lks. wide, 2 ft. deep, drains NW.
40.34	The ½ sec. cor. of secs. 10 and 11, monumented with a limestone, 12x10x3 ins., plainly mkd. and firmly set.
	At the corner point
	,