• * ·	Over nearly level land.
13.90	Wash, 15 lks. wide, 2 ft. deep, drains NW.
40.79	Point for the $\frac{1}{2}$ sec. cor. of secs. 2 and 3, at proportionate distance; there is no remaining evidence of the original corner.
v	Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T4S R55E
	S 3 S 2 1964
	raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor
45.40	Graded road, bears E. and W.
73.20	Trail road, bears NE. and SW.
81.38	The cor. of secs. 2, 3, 34 and 35 on the N. bdy. of the Tp., monumented with an iron post, $2\frac{1}{2}$ ins. diam., set, mkd. and witnessed as described in the field notes of the concurrent resurvey of T. 3 S., R. 55 E.
	Land, level. Soil, sandy loam. Undergrowth, greasewood and shadscale.
, , ,	From the cor. of secs. 10, 11, 14 and 15.
	N. 89° 44' W., bet. secs. 10 and 15.
	Over rolling land.
	Wash, 15 lks. wide, 2 ft. deep, drains N.
40.43	Point for the $\frac{1}{2}$ sec. cor. of secs. 10 and 15, at proportionate distance; there is no remaining evidence of the original corner.
· ·	Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground with brass cap mkd.
• .	T4S R55E <u>S 10</u> S 15 1964
	raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.
57.10	Trail road, bears NW. and SE.
80.86	The cor. of secs. 9, 10, 15 and 16, monumented with a limestone, 12x12x6 ins., firmly set and plainly mkd.
	At the corner point
	Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground with brass cap mkd.
	T4S R55E S 9 S 10 S16 S 15 1964

GPO 845-166