

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES, T. 4 S., R. 55 E.

CHAINS

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground with brass cap mkd.

T4S R55E
 $\frac{1}{4}$ S 3
 S 10
 1964

bury the original cornerstone alongside the iron post and raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.

N. $89^{\circ} 41'$ W., beginning new measurement.

40.45 The cor. of secs. 3, 4, 9 and 10:

Land, level.

Soil, sandy loam.

Undergrowth, greasewood and shadscale.

N. $0^{\circ} 11'$ W., bet. secs. 3 and 4.

Over level land.

34.20 Graded road, bears E. and W.

40.37 Point for the $\frac{1}{4}$ sec. cor. of secs. 3 and 4, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground with brass cap mkd.

T4S R55E
 $\frac{1}{4}$
 S 4 S 3
 1964

raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.

50.90 Trail road, bears ENE. and WSW.

80.98 The cor. of secs. 3, 4, 33 and 34 on the N. bdy. of the Tp., monumented with an iron post, $2\frac{1}{2}$ ins. diam., set, mkd., and witnessed as described in the field notes of the concurrent resurvey of T. 3 S., R. 55 E.

Land, level.

Soil, sandy loam.

Undergrowth, greasewood and shadscale.

From the cor. of secs. 9, 10, 15 and 16.

N. $89^{\circ} 23'$ W., bet. secs. 9 and 16.

Over rolling land.

24.90 Wash, 20 lks. wide, 2 ft. deep, drains NW.

40.07 Point for the $\frac{1}{4}$ sec. cor. of secs. 9 and 16, at proportionate distance; there is no remaining evidence of the original corner.