

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES, T. 4 S., R. 55 E.

CHAINS

bury the original cornerstone alongside the iron post and raise a mound of stone 2 ft. base, 1½ ft. high, W. of cor.

N. 0° 48' W., beginning new measurement.

5.20 Trail road, bears NW. and SE.

8.90 Trail road, bears NW. and SE.

40.00 The cor. of secs. 4, 5, 32 and 33 on the N. bdy. of the Tp., monumented with an iron post, 2½ ins. diam., set, mkd. and witnessed as described in the field notes of the concurrent resurvey of T. 3 S., R. 55 E.

Land, level.
Soil, sandy loam.
Undergrowth, greasewood and shadscale.

From the cor. of secs. 8, 9, 16 and 17.

N. 89° 38' W., bet. secs. 8 and 17.

Over rolling land.

20.20 Trail road, bears N. and S.

34.20 Wash, 15 lks. wide, 2 ft. deep, drains N.

40.37 Point for the ¼ sec. cor. of secs. 8 and 17, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post 28 ins. long, 2½ ins. diam., 24 ins. in the ground with brass cap mkd.

T4S R55E
¼ S 8
S 17
1964

raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.

63.20 Wash, 20 lks. wide, 2 ft. deep, drains N.

80.74 The cor. of secs. 7, 8, 17 and 18, monumented with a limestone, 12x8x6 ins., plainly mkd. and firmly set.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground with brass cap mkd.

T4S R55E
S 7 | S 8
S18 | S 17
1964

bury the original cornerstone alongside the iron post and raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.

Land, rolling.
Soil, sandy loam.
Undergrowth, greasewood and shadscale.