

DEPENDENT RESURVEY OF THE SOUTH BDY., T. 3 S., R. 55 E.

CHAINS

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground and in a collar of stone, with brass cap mkd.

T3S	R55E
<u>S 31</u>	<u>S 32</u>
S 6	S 5
T4S	
1964	

bury the original cornerstone alongside the iron post.

Land, level.

Soil, sandy loam.

Undergrowth, greasewood and shadscale.

N. 89° 58' W., bet. secs. 6 and 31.

Over level land.

34.20 Wash, 10 lks. wide, 2 ft. deep, drains ~~NE~~.

34.50 Graded road, bears NE. and SW.

40.29 The ¼ sec. cor. of secs. 6 and 31, monumented with a limestone, 6x6x6 ins., plainly mkd. and firmly set.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground with brass cap mkd.

T3S	R55E
<u>¼ S 31</u>	
S 6	
T4S	
1964	

bury the original cornerstone alongside the iron post and raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.

N. 86° 56' W., beginning new measurement.

41.42 Point for the cor. of Tps. 3 and 4 S., Rs. 54 and 55 E., at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground with brass cap mkd.

T3S	
R54E	R55E
<u>S 36</u>	<u>S 31</u>
S 1	S 6
T4S	
1964	

raise a mound of stone, 4 ft. base, 3 ft. high, S. of cor.

From which:

The ¼ sec. cor. of secs. 13 and 18, T. 3 S., Rs. 54 and 55 E., bears N. 0° 23' E., 280.24 chs. dist.