

DEPENDENT RESURVEY OF THE SOUTH BDY., T. 3 S., R. 55 E.

CHAINS

The $\frac{1}{2}$ sec. cor. of secs. 7 and 12, T. 4 S., Rs. 54 and 55 E., bears S. $0^{\circ} 16'$ E., 120.10 chs. dist.

The cor. of secs. 1, 2, 35 and 36, on the S. bdy. of T. 3 S., R. 54 E., bears S. $88^{\circ} 52'$ W., 79.55 chs. dist.

Land, level.

Soil, sandy loam.

Undergrowth, greasewood and shadscale.

Dependent Resurvey of the East Bdy. of T. 3 S., R. 55 E.,
Mount Diablo Meridian, Nevada

Re-establishment of the survey executed by
E. B. Monroe, Deputy Surveyor, in 1869
and retraced by Reilly and Magee,
Deputy Surveyors, in 1881.

Beginning at the cor. of Tps. 3 and 4 S., Rs. 55 and 56 E., heretofore described.

N. $0^{\circ} 24'$ E., bet. secs. 31 and 36.

Over level land.

31.40 Old Hwy., bears NW. and SE.

34.20 Nev. State Hwy. No. 25, bears N. $57^{\circ} 40'$ W., S. $57^{\circ} 40'$ E.

40.24 The $\frac{1}{2}$ sec. cor. of secs. 31 and 36, monumented with a wooden post, 2x2x24 ins. plainly mkd. and set.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground with brass cap mkd.

T3S
R55E $\frac{1}{2}$ R56E
S 36 | S 31
1964

raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor. and bury the original corner post alongside the iron post.

from which:

A house, bears N. $59^{\circ} 56'$ W., 14.64 chs. dist.

Timpahute Mill, bears N. $33^{\circ} 20'$ W., 12.98 chs. dist.

N. $0^{\circ} 21'$ E., beginning new measurement.

11.00 Trail road, bears N. 10° E. and S. 10° W.

18.70 Graded road, bears NE. and SW.

35.90 Wash, 20 lks. wide, 2 ft. deep, drains WNW.

39.91 The cor. of secs. 25, 30, 31 and 36, monumented with a wooden post, 2x2x18 ins., plainly mkd. and set.