

DEPENDENT RESURVEY OF THE NORTH BDY. OF T. 3 S., R. 55 E.

CHAINS

Land, level.
Soil, sandy.
Undergrowth, greasewood and shadscale.

N. 89° 59' W., bet. secs. 5 and 32.

Over small sand dunes.

20.00 Leave sand dunes, bears NW. and SE.

31.00 Graded road, bears N. and S.

40.33 The 1/4 sec. cor. of secs. 5 and 32, monumented with a granite stone, 14x12x6 ins., plainly mkd. and firmly set.

At the corner point

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground with brass cap mkd.

T2S	R55E
1/4 S	32
S	5
T3S	
1964	

bury the original cornerstone alongside the iron post and raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.

WEST, beginning new measurement.

40.31 The cor. of secs. 5, 6, 31 and 32, monumented with a granite stone, 8x6x4 ins., plainly mkd. and firmly set.

At the corner point

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground with brass cap mkd.

T2S	R55E
S31	S 32
S 6	S 5
T3S	
1964	

raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor. and bury the original cornerstone alongside the iron post.

Land, level.
Soil, sandy loam.
Undergrowth, greasewood and shadscale.

N. 89° 59' W., bet. secs. 6 and 31.

Over level land.

40.40 The 1/4 sec. cor. of secs. 6 and 31, monumented with a basalt stone, 18x12x10 ins., plainly mkd. and firmly set.

At the corner point

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground and in a collar of stone, with brass cap mkd.