

DEPENDENT RESURVEY OF THE NORTH BDY. OF T. 3 S., R. 55 E.

CHAINS

T2S R55E
 $\frac{1}{4}$ S 31
 S 6
 T3S
 1964

bury the original cornerstone alongside the iron post.

N. 86° 55' W., beginning new measurement.

14.20 Base of asc., bears NE. and SW.; asc. 430 ft. over E. slope.

34.80 Top of ridge, bears NE. and SW.; desc. 90 ft. over W. slope.

41.30 The cor. of Tps. 2 and 3 S., Rs. 54 and 55 E., monumented with a granite stone, 18x12x6 ins. plainly mkd. and firmly set.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 15 ins. in the ground to bedrock and in a mound of stone, 4 ft. base to top, with brass cap mkd.

T2S
 R54E R55E
 S 36 S 31
 S 1 S 6
 T3S
 1964

bury the original cornerstone alongside the iron post.

Land, level, broken.
 Soil, sandy loam, rocky.
 Undergrowth, greasewood and shadscale.

Dependent Resurvey of the Subdivisional Lines of T. 3 S., R. 55 E., Mount Diablo Meridian, Nevada

Re-establishment of the survey executed by Reilly and Magee, Deputy Surveyors, in 1881.

From the cor. of secs. 1, 2, 35 and 36, on the S. bdy. of the Tp.

N. 0° 20' E., bet. secs. 35 and 36.

Over level land.

22.00 Trail road, bears N. 70° E., and S. 70° W.

40.31 Point for the ¼ sec. cor. of secs. 35 and 36, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground with brass cap mkd.