

DEPENDENT RESURVEY, E. BDY., T. 37 N., R. 41 E.

CHAINS

T37N
R41E R42E
S 1 | S 6
S 12 | S 7
1963

raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.

Land, rolling.

Soil, sandy loam and rocky.

Undergrowth, sagebrush, shadscale and rabbitbrush.

N. 0° 05' E., bet. secs. 1 and 6:

Over rolling land, through medium undergrowth; along an E. slope.

- 3.50 Ravine, drains SE.; asc. 130 ft. over a S. slope.
- 13.50 Spur, bears SW.; desc. 40 ft. over a NW. slope.
- 25.30 Trail road, bears NE. and SW.; continue over rolling land.
- 38.80 Spur, bears SE.
- 41.76 Point for the $\frac{1}{4}$ sec. cor. of secs. 1 and 6, at proportionate distance; there is no remaining evidence of the original corner.
- Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 18 ins. in the ground to bedrock, and in a mound of stone to cap, $3\frac{1}{2}$ ft. base, with brass cap mkd.

T37N
R41E R42E
 $\frac{1}{4}$
S 1 | S 6
1963

Desc. 30 ft. over a NE. slope.

- 56.90 Ravine, drains SE.; asc. 370 ft. over a S. slope.

- 83.52 The cor. of Tps. 37 and 38 N., Rs. 41 and 42 E., monumented with an unmarked wooden post, 1x1x30 ins., loosely set in a mound of stone.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 10 ins. in the ground to bedrock, and in a mound of stone to cap, 6 ft. base, with brass cap mkd.

T38N
R41E R42E
S 36 | S 31
S 1 | S 6
T37N
1963