

DEPENDENT RESURVEY, N. BDY., T. 37 N., R. 41 E.

CHAINS

37.97 The 1/4 sec. cor. of secs. 5 and 32, monumented with a granite stone, 18x10x4 ins., firmly set and plainly mkd. 1/4 on the N. face, with a mound of stone to S.

At the corner point

Set an iron post, 36 ins. long, 1 in. diam., 10 ins. in the ground to bedrock, and in a mound of stone to cap, 4 ft. base, with brass cap mkd.

T38N R41E  
1/4 S 32  
S 5  
T37N  
1963

bury the original cornerstone alongside the iron post.

N. 89° 55' W., beginning new measurement.

Desc. 370 ft. over a NW. slope.

16.90 Ravine, drains N.; desc. 320 ft. over a NW. slope.

40.55 The cor. of secs. 5, 6, 31 and 32, monumented with an unmarked wooden post, 2x2x36 ins., loosely set in a mound of stone.

At the corner point

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T38N R41E  
S 31 | S 32  
S 6 | S 5  
T37N  
1963

reset the wooden post alongside the iron post, and raise a mound of stone, 4 ft. base, 3 ft. high, W. of cor.

Land, mountainous.

Soil, sandy clay loam and rocky.

Undergrowth, sagebrush and cheat grass.

N. 89° 51' W., bet. secs. 6 and 31.

Over rolling land, through medium undergrowth; desc. 190 ft. over a NW. slope.

13.30 Stream 10 lks. wide, 1 ft. deep, course SW.; base of mountains, bears NE. and SW.; desc. 30 ft. over a SW. slope.

18.90 Wash, 20 lks. wide, 2 ft. deep, drains SW.; desc. 60 ft. over a SW. slope.

34.00 Wash, 20 lks. wide, 2 ft. deep, drains SW.