DEPENDENT RESURVEY, S. BDY., T. 37 N., R. 41 E.

CHAINS	
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. T37N R41E ¼ S 32 S 5 T36N 1963 raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor. Asc. 40 ft. over a SE. slope.
54.00	Wash, 20 lks. wide, 3 ft. deep, drains S.; asc. 30 ft. over a SE. slope.
64.60	Wash, 30 lks. wide, 3 ft. deep, drains SE.; asc. 20 ft. over an E. slope.
77.18	The cor. of secs. 5, 6, 31 and 32, monumented with a sandstone, 12x6x4 ins., firmly set and plainly mkd. with 5 notches on the E. face, and 6 notches on the S. face. At the corner point Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. T37N R41E S 31 | S 32 S 6 | S 5 T36N 1963 bury the original cornerstone alongside the iron post, and raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor. Land, rolling. Soil, sandy loam and rocky. Undergrowth, sagebrush.
	S. 89° 33' W., bet. secs. 6 and 31. Over rolling land, through medium undergrowth; asc. 150 ft. over an E. slope.
14.30	Top of knoll; desc. 60 ft. over a W. slope.
26.90	Ravine, drains S.; asc. 200 ft. over an E. slope.
41.56	Top of knoll.
41.56	The ¼ sec. cor. of secs. 6 and 31, monumented with an unmarked lava stone, 12x10x6 ins., firmly set in a mound of stone. At the corner point