

DEPENDENT RESURVEY, E. BDY., T. 37 N., R. 42 E.

CHAINS

Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.

T37N	
R42E	R43E
S 12	S 7
S 13	S 18
1963	

raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.  
Land, nearly level.  
Soil, sandy loam and alkaline.  
Undergrowth, greasewood, shadscale and budsage.

N. 0° 11' W., bet. secs. 7 and 12.

Over nearly level land, through medium undergrowth.

40.32 Point for the ¼ sec. cor. of secs. 7 and 12, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.

T37N	
R42E	R43E
S 12	S 7
1963	

set a stone, 18x14x12 ins., 8 ins. in the ground, W. of cor.

58.40 Trail road, bears N. 70° E. and S. 70° W.

62.40 State Highway No. 18, gravel, bears N. 75° E. and S. 75° W.

80.64 Point for the cor. of secs. 1, 6, 7 and 12, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.

T37N	
R42E	R43E
S 1	S 6
S 12	S 7
1963	

raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.  
Land, nearly level.  
Soil, sandy, clay and alkaline.  
Undergrowth, greasewood and sagebrush.

N. 0° 11' W., bet. secs. 1 and 6.

Over nearly level land, through medium undergrowth.

40.32 Point for the ¼ sec. cor. of secs. 1 and 6, at proportionate distance; there is no remaining evidence of the original corner.