

SURVEY OF SUBDIVISIONAL LINES, T. 37½ N., R. 43 E.

CHAINS

From this corner, the ¼ sec. cor. of sec. 5, T. 37 N., R. 43 E., an iron post, 2½ ins. diam., set, mkd. and witnessed as described in the field notes of the concurrent resurvey of T. 37 N., R. 43 E., bears S. 89° 39' E., 0.72 ch. dist.

The point for the S. ¼ sec. cor. of sec. 31 is on the N. bdy. of T. 37 N., R. 43 E. and 40.00 chs. west of the cor. of secs. 5, 6, 31 and 32.

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T37½N. R43E

¼ S 31.

T37N

1963

raise a mound of stone, 2½ ft. base, 2 ft. high, N. of cor.

From this corner, the ¼ sec. cor. of sec. 6, T. 37 N., R. 43 E., an iron post, 2½ ins. diam., set, mkd., and witnessed as described in the field notes of the concurrent resurvey of T. 37 N., R. 43 E., bears N. 89° 39' W., 0.76 ch. dist.

GENERAL DESCRIPTION

The general elevation of this township is about 4500 ft. above sea level, consisting of nearly level to gently rolling land. The soil is sandy loam. The vegetation consists of shadscale, sagebrush and greasewood.

Principal users of the area are cattlemen and access into the township is provided by improved and unimproved roads.