

DEPENDENT RESURVEY, N. BDY., T. 38 N., R. 43 E.

CHAINS
39.48

The cor. of secs. 5, 6, 31 and 32, monumented with a basalt stone, 10x6x4 ins., firmly set in a mound of stone and plainly mkd. with 5 notches on the E. face and 1 notch on the W. face.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T39N	R43E
S 31	S 32
S 6	S 5
T38N	
1963	

bury the original cornerstone alongside the iron post and raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.

Land, gently rolling.

Soil, sandy loam.

Undergrowth, sagebrush and shadscale.

N. 89° 10' W., bet. secs. 6 and 31.

Over gently rolling land, through medium undergrowth.

2.30 Trail road, bears SE. and NW.

32.70 Wash, 10 lks. wide, 1 ft. deep, drains SE.

39.27 Point for the ¼ sec. cor. of secs. 6 and 31, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T39N	R43E
¼ S 31	
S 6	
T38N	
1963	

raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.

51.80 Wash, 20 lks. wide, 2 ft. deep, drains SE.

77.77 The cor. of Tps. 38 and 39 N., R. 43 E., monumented with the remains of the original squared wooden post, loosely set in a mound of earth.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T39N	
R42E	R43E
S 36	S 31
	S 6
T38N	
1963	