

DEPENDENT RESURVEY, S. BDY., T. 38 N., R. 43 E.

CHAINS

Land, nearly level.
Soil, sandy loam.
Undergrowth, sagebrush, greasewood and shadscale.

S. 88° 59' W., along the S. bdy. of sec. 31.

Over gently rolling land, through medium undergrowth.

- 1.70 Wash, 10 lks. wide, 1 ft. deep, drains S.
15.20 Wash, 10 lks. wide, 2 ft. deep, drains S.
28.50 Wash, 10 lks. wide, 1 ft. deep, drains S.
34.30 Trail road, bears N. and S.
39.59 Point for the $\frac{1}{4}$ sec. cor. on the N. bdy., of sec. 31,
40.00 chs. in departure from the cor. of secs. 31 and 32,
T. 37 $\frac{1}{2}$ N., R. 43 E.

Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 24 ins. in
the ground, with brass cap mkd.

T38N R43E

$\frac{1}{4}$ S 31
T37 $\frac{1}{2}$ N
1963

raise a mound of stone, 2 $\frac{1}{2}$ ft. base, 2 ft. high, S. of
cor.

- 40.02 The $\frac{1}{4}$ sec. cor. on the S. bdy. of sec. 31, monumented
with a small mound of stone, There is no evidence of a
wooden post or marked stone, This is the best available
evidence of the original corner.

At the corner point

Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 22 ins.
in the ground, with brass cap mkd.

T38N R43E

$\frac{1}{4}$ S 31

T37 $\frac{1}{2}$ N
1963

raise a mound of stone, 3 ft. base, 2 ft. high, N. of
cor.

S. 89° 19' W., beginning new measurement.

Over gently rolling land.

- 1.00 Wash, 10 lks. wide, 1 ft. deep, drains S. 20° E.
20.60 Wash, 10 lks. wide, 1 ft. deep, drains S. 10° E.
39.86 The cor. of Tps. 37 $\frac{1}{2}$ and 38 N., R. 43 E., monumented with
a squared wooden post, 2x2x24 ins. long, loosely set in
a mound of earth.

At the corner point