DEPENDENT RESURVEY OF A PORTION OF THE WEST BOUNDARY OF TOWNSHIP 3 NORTH, RANGE 45 EAST

	OF TOWNSHIP 3 NORTH, RANGE 45 EAST
CHAINS	N. 0° 28' E., bet secs. 7 and 12.
	Asc. 80 ft. over gentle S. slope.
40.28	The ½ sec. cor. of secs. 7 and 12, monumented with a lava stone, 8x6x5 ins., plainly mkd. and firmly set.
	At the corner point
	Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground and in a collar of stone, with brass cap mkd.
	T3N R44E R45E ½
	S 12 S 7 1965
	bury the original cornerstone alongside the iron post.
	N. 0° 22' W., beginning new measurement.
	Asc. 110 ft. over S. slope.
40.15	The cor. of secs. 1, 6, 7 and 12, monumented with a granite stone, 18x12x10 ins., plainly mkd. and embedded in a circle of stones.
	At the corner point
	Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 14 ins. in the ground and in a mound of stone, $3\frac{1}{2}$ ft. base to top, with brass cap mkd.
	T3N R44E R45E <u>S 1 S 6</u> S 12 S 7 1965
	bury the original cornerstone alongside the iron post.
	Land, low rolling. Soil, light gravel, sandy clay. Timber, none; undergrowth, sage, salt brush and grama grass.
	N. 0° 06' W., bet. secs. 1 and 6.
	Slope changes to SW.slope; asc. 170 ft.
40.12	The $\frac{1}{4}$ sec. cor. of secs. 1 and 6, monumented with a volcanic stone, $10 \times 10 \times 8$ ins., dimly mkd. and firmly set.
	At the corner point
	Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 8 ins. in the ground and in a mound of stone, 4 ft. base to top, with brass cap mkd.