DEPENDENT RESURVEY OF A PORTION OF THE **SUBDIVISIONAL LINES** TOWNSHIP 3 NORTH, RANGE 45 EAST

	TOWNSHIP 3 NORTH, RANGE 45 EAST
CHAINS	T3N R45E
	S 35 S 36 1965
	bury the original cornerstone alongside the iron post.
	N. 3° 58' W., bet. secs. 35 and 36.
	Over broken land covered with sage and grass; asc. 90 ft. over a steep S. slope.
8.50	Crest of mesa top; desc. 290 ft. over a N. slope.
39.76	The cor. of secs. 25, 26, 35 and 36, monumented with a lava stone, 16x12x10 ins., plainly mkd. and set in a collar of stone.
	At the corner point
	Set an iron post, 28 ins. long, 2½ ins. diam., 16 ins. in the ground and in a mound of stone, 3½ ft. base to top, with brass cap mkd.
	T3N R45E S 26 S 25 S 35 S 36 1965
	bury the original cornerstone alongside the iron post.
	Land, broken. Soil, rocky and sandy clay. Timber, scattered juniper. Undergrowth, sage, salt brush and grass.
	From the cor. of secs. 25, 30, 31 and 36 on the east boundary of the township, an iron post, 2½ ins. diam., set, mkd. and witnessed as described in the concurrent resurvey of T. 3 N., R 46 E.
	N. 85° 52' W., bet. secs. 25 and 36.
	Over high rolling hills; asc. 20 ft. over an E. slope.
10.40	Wash, 30 1ks. wide, 2 ft. deep, drains SE.; asc. 100 ft. over a NE slope.
31.10	Wash, 20 lks. wide, 2 ft. deep, drains SE.; asc. 90 ft. over an E. slope.
35.43	Point for the ½ sec. cor. of secs. 25 and 36, at proportionate distance; there is no remaining evidence of the original corner.
	Set an iron post, 36 ins. long, 1 in. diam., 12 ins. in the ground and in a mound of stone, 3½ ft. base to top, with brass cap mkd.
	T3N R45E 1 <u>S 25</u> S 36 1965