

DEPENDENT RESURVEY OF A PORTION OF THE W. BDY. OF
T. 3 N., R. 46 E.

CHAINS

- Over high, rolling land, asc. 60 ft. over a SW. slope.
4.60 Ridge, bears NW. and SE.; desc. 140 ft. over a N. slope.
16.30 Draw, drains E.; asc. 80 ft. over S. slope.
21.50 Spur, slopes E.; desc. 110 ft. over N. slope.
37.50 Wash, 20 lks. wide, 2 ft. deep, drains SE.; asc. 20 ft.
over a S. slope.
40.30 Bladed road, bears E. and W.
40.43 The cor. of secs. 19, 24, 25 and 30, monumented with a
trap stone, 8x8x6 ins., plainly mkd. and in a circle of
stone.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in
the ground and in a collar of stone, with brass cap mkd.

T3N	
R45E	R 46E
S 24	S 19
S 25	S 30
1965	

bury the original cornerstone alongside the iron post.

Land, high, rolling.

Soil, stony clay.

Timber, none.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL
LINES OF T. 3 N., R. 46 E., MDM, NEVADA

Re-establishment of the Survey Executed by
N. L. Berdan, Deputy Surveyor, in 1883

The cor. of secs. 13, 18, 19 and 24, on the E. bdy. of
the Tp. monumented with a lava stone, 22x12x8 ins., dimly
mkd. and set in a circle of stone.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in
the ground and in a collar of stone, with brass cap mkd.

T3N	
R46E	R47E
S 13	S 18
S 24	S 19
1965	

bury the original cornerstone alongside the iron post.