DEPENDENT RESURVEY OF EAST BOUNDARY, T. 8 N., R. 41 E.

CHAINS

Dependent Resurvey of East Bounday, T. 8 N., R. 41 E., M.D.M., Nevada

Re-establishment of the Survey Executed by A. Hatch, D. H. Barker and E. L. Bridges, Deputy Surveyors, in 1873.

From the cor. of Tps. 7 and 8 N., Rs. 41 and 42 E., hereinafter described.

N. 0° 44 $^{\circ}$ E., bet. secs. 31 and 36.

Over rolling land, covered with scrub sage and salt brush.

Asc. 100 ft. over a S. slope.

39.76 The % sec. cor. of secs. 31 and 36, monumented with a lava stone, 15x9x6 ins., plainly mkd. and firmly set.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 20 ins. in the ground, and in a collar of stone, with brass cap mkd.

T8N R41E R42E \$ 36 | S 31 1963

bury the original cornerstone alongside the iron post.

Independent Resurvey of a Portion of the East Bdy. of T. 8 N., R. 41 E.

Superseding the Survey Executed by A. Hatch, D. H. Barker and E. L. Bridges, Deputy Surveyors, in 1873.

Diligent search was made for all original corners for the next 2 miles along this boundary. All corners that were found are described, and the connections are entered in the record, after which all traces of the original corners were destroyed.

From the $\frac{1}{4}$ sec. cor. of sec. 31 and 36, heretofore described.

NORTH, along the east bdy. of sec. 36, T. 8 N., R. 41 E.

Over rolling land covered with scrub sage and salt brush.

13.00 Limestone spur, slopes E.; desc. 30 ft. over N. slope.

40.00 Point for the cor. of secs. 25 and 36, T. 8 N., R. 41 E.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, and in a collar of stone, with brass cap mkd.

, and an electric, mass, mass, and