

INDEPENDENT RESURVEY OF A PORTION OF THE EAST BOUNDARY,  
T. 8 N., R. 41 E.

CHAINS	
	<p>NORTH, along the E. bdy. of sec. 24.</p> <p>Over rolling land covered with sage and salt brush.</p>
0.72	<p>The closing corner of secs. 19 and 30, T. 8 N., R. 42 E., hereinafter described.</p> <p>Asc. 110 ft. over a S. slope.</p>
40.00	<p>Point for the <math>\frac{1}{4}</math> sec. cor. of sec. 24, T. 8 N., R. 41 E.</p> <p>Set an iron post, 28 ins. long, <math>2\frac{1}{2}</math> ins. diam., 20 ins. in the ground, and in a collar of stone, with brass cap mkd.</p> <div style="text-align: center;"> <p>T8N R41E   R42E <math>\frac{1}{4}</math>   S 24   1963</p> </div> <p>Land, rolling. Soil, stony and sandy clay. Timber, sparse juniper and pinon. Undergrowth, sage, salt brush and bunch grass.</p> <hr/> <p style="text-align: center;">Dependent Resurvey of a Portion of the South Boundary, T. 8 N., R. 42 E.</p> <hr/> <p style="text-align: center;">Re-establishment of the Survey Executed by A. Hatch, D. H. Barker and E. L. Bridges, Deputy Surveyors, in 1873.</p> <hr/> <p>The <math>\frac{1}{4}</math> sec. cor. of secs. 4 and 33, monumented with a squared post, plainly mkd. and firmly set.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, <math>2\frac{1}{2}</math> ins. diam., 20 ins. in the ground, and in a collar of stone, with brass cap mkd.</p> <div style="text-align: center;"> <p>T8N R42E <math>\frac{1}{4}</math> <math>\frac{S}{S}</math> <math>\frac{33}{4}</math> T7N 1963</p> </div> <p>bury original corner stake alongside the iron post.</p> <p>N. 89° 41' W., bet. secs. 4 and 33.</p> <p>Over gentle rolling land covered with scrub sage and salt brush.</p>
15.00	<p>Graded road, bears N. and S.</p>
40.28	<p>Point for the cor. of secs. 4, 5, 32 and 33, at proportionate distance; there is no remaining evidence of the original corner.</p>