

DEPENDENT RESURVEY OF A PORTION OF THE S. BDY., T. 8 N., R. 42 E.

CHAINS

Asc. 20 ft. over a NE. slope.

32.60 Wash, 30 lks. wide, 2 ft. deep, drains SE.

40.25 The $\frac{1}{4}$ sec. cor. of secs. 6 and 31, monumented with a lava stone, 20x12x8 ins., plainly mkd. and firmly set.

At the corner point

Set an iron post, 36 ins. long, 1 ins. diam., 10 ins. in the ground, and in a mound of stone $3\frac{1}{2}$ ft. base to top, with brass cap mkd.

	T8N	R42E
$\frac{1}{4}$	S	31
	S	6
	T7N	
	1963	

bury original cornerstone alongside the iron post.

S. $89^{\circ} 40'$ W., beginning new measurement.

8.80 Unimproved road, bears ENE. and WSW.

36.80 Wash, 40 lks. wide, 2 ft. deep, drains SW.

40.17 The cor. of Tps. 7 and 8 N., Rs. 41 and 42 E., monumented with a stone, 30x20x12 ins., plainly mkd. and firmly set.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 10 ins. in the ground, and in a mound of stone 4 ft. base, 16 ins. high, with brass cap mkd.

	T8N	
	R41E	R42E
	S 36	S 31
	S 1	S 6
	T7N	
	1963	

bury original cornerstone alongside the iron post.

Land, gentle rolling.

Soil, stony, mixed with sandy clay.

Undergrowth, scrub sage and salt brush.

Dependent Resurvey of a Portion of the East Boundary,
T. 8 N., R. 42 E.,
M.D.M., Nevada

Re-establishment of the Survey Executed by
C. C. Tracy, Deputy Surveyor, in 1867

The $\frac{1}{4}$ sec. cor. of secs. 19 and 24, on the E. bdy. of T. 8 N., R. 42 E., monumented with a squared post, 3 ft. long, plainly mkd. and set in a circle of stone.

At the corner point