

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES, T. 8 N., R. 42 E.

CHAINS	
20.00	Base of gentle E. slope; leave dry lake bed.
39.76	<p>The $\frac{1}{4}$ sec. cor. of secs. 11 and 14, monumented with a granite stone, 20x6x4 ins., plainly mkd. and firmly set.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 20 ins. in the ground, and in a collar of stone, with brass cap mkd.</p> <div style="text-align: center;"> <p>T8N R42E</p> <p>$\frac{1}{4}$ $\frac{S}{S}$ $\frac{11}{14}$</p> <p>1963</p> </div> <p>bury the original cornerstone alongside the iron post, and deposit broken glass around the iron post.</p> <hr/> <p>N. $89^{\circ} 26'$ W., beginning new measurement.</p> <p>Ascend 40 ft. over an east slope.</p>
40.91	<p>The cor. of secs. 10, 11, 14 and 15.</p> <p>Land, gently rolling.</p> <p>Soil, clay and stony.</p> <p>Undergrowth, grease wood and scrub sage.</p> <hr/> <p style="text-align: center;">Survey of a Portion of the Subdivisional Lines, T. 8 N., R. 42 E.</p> <hr/> <p>NORTH, bet. secs. 10 and 11.</p> <p>Over mountainous land, covered with sage and salt brush.</p> <p>Asc. 290 ft. over a broken S. slope.</p>
40.00	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 10 and 11.</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 6 ins. to bed rock, and in a mound of stone, 4 ft. base to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>T8N R42E</p> <p>$\frac{1}{4}$</p> <p>S10 S 11.</p> <p>1963</p> </div> <p>Asc. 110 ft. over a S. slope.</p>
48.00	Spur, slopes SE.; desc. 50 ft. over a NE. slope.
51.10	Small wash in bottom of draw, drains SE.; asc. 330 ft. over a steep S. slope.
67.50	Top of rocky outcropping, slope changes to W. slope; asc. 170 ft.
80.10	Point for the cor. of secs. 2, 3, 10 and 11, established due NORTH from the cor. of sec. 10, 11, 14 and 15, and due WEST from the $\frac{1}{4}$ sec. cor. of secs. 2 and 11.