SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES, T. 8 N., R. 42 E.		
	CHAINS	
	41.30	Wash, 25 lks. wide, 2 ft. deep, drains SE.; asc. 40 ft. over an E. slope.
	46.00	Ridge, bears N. and S.; desc. 20 ft. over a W. slope.
	50.10	Wash, 1.00 chain wide, 2 ft. deep, drains S.; asc. 20 ft. over an E. slope.
	56.80	Wash, 20 1ks. wide, 2 ft. deep, drains SSE.
	59.00	Top of ascent; desc. 20 ft. over W. slope.
	73.58	Intersect the west boundary.
		Point for the closing corner of secs. 30 and 31.
		Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 20 ins. in the ground, and in a collar of stone, with brass cap mkd.
		T8N T8N R41E R42E S 25 S 30 C S 31 C 1963
	• .	from which
	·	The cor. of secs. 25 and 36, T. 8 N., R. 41 E., heretofore described, bears SOUTH, 3.82 chs. dist.
		The ½ sec. cor. of sec. 25, T. 8 N., R. 41 E., only, heretofore described, bears NORTH, 36.18 chs. dist.
		Land, low rolling. Soil, stony, sandy clay. Undergrowth, sage and salt brush.
		From the cor. of secs. 29, 30, 31 and 32.
		NORTH, bet. secs. 30 and 29.
		Over gentle rolling land covered with sage and salt brush.
		Asc. 20 ft. over E. slope.
	19.00	Wash, 35 lks. wide, 2 ft. deep, drains SE.; asc. over S. slope 60 ft.
	40.00	Point for the ½ sec. cor. of secs. 29 and 30.
		Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 12 ins. in the ground, and in a mound of stone, $3\frac{1}{2}$ ft. base to top, with brass cap mkd.
		T8N R42E
		S30 S 29 1963
		Asc. 20 ft. over a S. slope.
	43.50	Spur, slopes SE.; desc. 60 ft. over a NE. slope.